

ART OIL GRAPHITE PASTE

DESCRIPTION

ART OIL GRAPHITE PASTE is a lubricating paste containing a high amount of graphite.

FIELDS OF USAGE

It can be used in the lubrication of steel ropes, elevators, coils, and ship ropes, where there is excessive friction.

PROPERTIES

- Protects the system against rust and corrosion.
- Provides excellent wear protection in metal frictions.
- Reduces maintenance costs and malfunctions and increases production efficiency.
- Provides great lubrication.
- Shows resistance under high pressure and heat.

STORAGE

- Packaging should be stored in covered areas with the lids tightly closed.
- It should not be exposed to the direct effects of sun heat and heat sources.
- The ambient temperature should not exceed 60°C.
- Maximum two pallets should be stored on top of each other.
- Consult the Material Safety Data Sheet (MSDS) for more information.

SUBSTANTIAL AND CHEMICAL PROPERTIES

	STANDARD	GRAPHITE PASTE
NLGI Number	-	2-3
Color	-	Black
Soap Type	-	Soap Free
Thickener Type	-	Bentonite
Dropping Point, min. (°C)	ASTM D 566	>300
Operating Temperature, max. (°C)	-	> 200

(* Values may differ from production to production.

HEALTH AND SAFETY

Used waste products should not be dumped into underground and above-ground water sources, sewer connections, and garbage. Prolonged contact with used oils can cause skin diseases. Therefore, sterile gloves should be used. If the used oil comes into contact with the skin, that area should be washed immediately with plenty of water and soap. If irritation or redness occurs in case of skin contact, seek medical advice immediately.